# **PERMA-CRETE®** MASONRY COATINGS PRODUCT SELECTOR & SYSTEM GUIDE







## A GUIDE TO CHOOSING THE RIGHT COATING **SYSTEM FOR YOUR MASONRY NEEDS**

AT PPG, WE UNDERSTAND THAT TIME CONSTRAINTS, BUDGET REQUIREMENTS AND TOUGH SUBSTRATE CONDITIONS can present complications on job sites. The PERMA-CRETE® Masonry Coatings line can help you overcome these obstacles with confidence. Perma-Crete's unrivaled performance characteristics equip the line to meet the demands of an unprecedented array of surface conditions to solve job site issues and prevent future problems.

Proper selection and use of coatings for concrete should lead to a successful and aesthetically attractive job. A wide variety of coatings are available for every kind of masonry substrate encountered in the construction market.

This Perma-Crete Product Selector & System Guide has been designed to provide a simple and easy way for you to find solutions to all of your concrete and masonry needs by categorizing the *Perma-Crete* family of products into the following groups:

**PATCHING COMPOUNDS** PRIMERS **PRIMER/SEALERS BLOCK FILLER CLEAR TOPCOAT SEALER ELASTOMERIC TOPCOAT TEXTURED COATINGS VERTICAL ABOVE GRADE TOPCOATS CONCRETE STAIN** WATER REPELLENT

This Product Selector & System Guide focuses on some typical concrete and masonry end uses and specific product recommendations for common masonry surface problems and conditions for both commercial and residential applications. Use this Product Selector & System Guide to find the best coating for your concrete structure.

#### **KEY**



Capable



Waterborne Temperature Acrylic

Acrvlic



FFD Credits



Silane/

Siloxane



Hot Tire Resistant

# **PERMA-CRETE PRODUCTS BY CATEGORY**

## **PATCHING COMPOUNDS**

4-1000, 4-1001, 4-1002, 4-1003

PERMA-CRETE® Patching Compounds are waterborne acrylic patches designed to fill cracks and voids on masonry surfaces to prevent moisture intrusions. These patches can be topcoated with any PPG *Perma-Crete* acrylic latex primer or topcoat.



## PERMA-CRETE® PITT-FLEX® ELASTOMERIC PATCHING COMPOUND

#### 4-1000, 4-1001, 4-1002, 4-1003

- A premium high-technology product formulated for patching larger cracks (1/16" to 1/4") on masonry surfaces
- Patches cracks, voids and openings in masonry and stucco surfaces
- · Compatible with acrylic coatings
- · Ideal for use on concrete, stucco and masonry
- · Knife Grade Smooth & Textured
- · Brush Grade Smooth & Textured
- Interior/Exterior
- · Available in 1-gallon and quarts within select products





Masonry primers protect the finish coat from the alkalinity of the masonry, reduce the tendency for efflorescence and provide a smooth, sealed surface. PERMA-CRETE<sup>®</sup> primers offer specific solutions to ensure a quality appearance, value and efficiency when paired with quality *Perma-Crete* topcoats.



## PERMA-CRETE® INT/EXT ALKALI RESISTANT PRIMER

#### 4-603XI

- · A premium alkali-resistant primer
- Provides excellent sealing and stain blocking performance
- Apply to fresh concrete with a surface pH of 7 to 13; minimizes salt deposits
- Ideal for use on brick, concrete, concrete block (CMU), wood, cinder block, fiber cement siding, masonry surfaces, stucco, tilt-up and wallboard
- MPI approved in category 3
- Interior/Exterior
- · Available in 1- and 5-gallon pails
- VOC compliant in all regulated areas (<100 g/L)



Scan to view the Technical Data Sheet



## PERMA-CRETE® EXTERIOR CONCRETE & STUCCO PRIMER

#### 4-503

- · An alkali-resistant primer
- Apply to fresh concrete with a surface pH of 7 to 13; minimizes salt deposits
- Ideal for use on brick, concrete, concrete block (CMU), cinder block, fiber cement siding, masonry surfaces, stucco, tilt-up and wallboard
- MPI approved in category 3
- Exterior
- · Available in 5-gallon pails
- VOC compliant in all regulated areas (<100 g/L)



## PRIMER / SEALERS 4-808, 4-809

Prevent adhesion problems and delamination with PERMA-CRETE® Interior / Exterior Acrylic Masonry Sealers. These fast-drying, waterborne, clear or pigmented acrylic sealers penetrate and bind chalky, powdery, or porous surfaces, especially badly weathered cement shingles, stucco, or existing topcoats that have deteriorated over time. This chemical-resistant sealer provides a firm surface for application of exterior latex paints.



## PERMA-CRETE® INT/EXT ACRYLIC MASONRY SURFACE SEALER

4-808, 4-809

- · Clear or pigmented waterborne acrylic sealer
- Fast drying
- Deeply penetrates and seals new, porous surfaces and old, dusty or chalky paint films and substrates
- Ideal for use on brick, concrete, concrete block (CMU), cinder block, fiber cement siding, masonry surfaces and stucco
- Interior/Exterior
- · Available in 1- and 5-gallon pails
- · VOC compliant in all regulated areas (<250 g/L)





PERMA-CRETE<sup>®</sup> Concrete Block & Masonry Surfacer is a premium interior/exterior, light weight, acrylic latex block filler and surfacer for all types of properly prepared concrete and masonry surfaces



## **PERMA-CRETE® LTC LOW TEMP. BLOCK SURFACE FILLER**

#### 4-100XI

- A premium lightweight, acrylic latex block filler and surfacer
- · Smooths, fills and levels surfaces
- Apply to fresh concrete with a surface pH of 7 to 13; minimizes salt deposits
- Ideal for use on brick, concrete, concrete block (CMU), cinder block, fiber cement siding, masonry surfaces, stucco and tilt-up
- MPI apporved in category 4
- Interior/Exterior
- $\cdot$  Available in 5-gallon pails
- · VOC compliant in all regulated areas (<100 g/L)



## CLEAR TOPCOAT SEALER 4-6200XI

Protect and beautify your concrete surface with low-VOC PERMA-CRETE® PLEX-SEAL<sup>™</sup> WB Clear Sealer. *Plex-Seal* sealer resists hot tire pick-up, minimizing stains and discoloration on traffic surfaces and decreasing maintenance costs. This ready-to-use concrete sealer is moisture resistant and has excellent adhesion, preventing the coating from peeling and cracking thereby extending the substrate life.



## PERMA-CRETE® PLEX-SEAL™ INT/EXT CLEAR SEALER

#### 4-6200XI

- · Clear, film-forming sealer
- · Water repellent
- $\cdot$  For use on above-grade, vertical and horizontal surfaces
- Ideal for use on masonry, concrete, brick, stone, stucco, mortar, non-glazed ceramic tile and exposed aggregate
- Interior/Exterior
- · Available in 1- and 5-gallon pails
- MPI #99 approval; Meets strict performance and aesthetic requirements
- · VOC compliant in all regulated areas (<100 g/L)



## **ELASTOMERIC TOPCOAT** 4-110XI, 4-140XI

Elastomerics have the ability to bridge cracks that develop in a masonry wall. Specially formulated for flexibility, elastomerics can stretch and contract to accommodate substrate movement resulting from temperature change. This flexible crack-bridging ability results in a long-lasting, uniform finish that enhances the appearance of the masonry building.



#### PERMA-CRETE® PITT-FLEX® ELASTOMERIC COATING 4-110XI, 4-140XI

- · 100% acrylic, high build elastomeric
- Smooth finish
- · For use on horizontal and vertical, above-grade surfaces
- · Bridges cracks and masks surface imperfections
- Apply to fresh concrete with a surface pH of 7 to 13; minimizes salt deposits
- Resists wind-driven rain with two coats @ 6.5 mils each
- Ideal for use on brick, concrete, concrete block (CMU), cinder block, fiber cement siding, masonry surfaces, stucco and tilt-up
- Interior/Exterior
- · Available in 1 and 5-gallon pails
- $\cdot$  MPI #113 approval; Meets strict performance and aesthetic requirements
- · VOC compliant in all regulated areas (<50 g/L)



## **TEXTURED COATINGS** 4-50, 4-60, 4-65, 4-70

Textured coatings are designed to be applied over concrete, cinder block and stucco surfaces to create a protective layer and provide waterproofing with enough flexibility to bridge gaps and cracks. The texture of the coating also helps aesthetically by hiding surface imperfections.



## PERMA-CRETE® 100% ACRYLIC TEXTURE COATING - FINE

#### 4-50

- · 100% acrylic texture coating
- · Fine texture
- For use on horizontal and vertical, abovegrade, pre-cast and tilt-up masonry substrates
- Minimizes surface imperfections
- · Provides a decorative appearance
- Ideal for use on brick, concrete, concrete block (CMU), masonry, metal, plaster, plywood, stone and stucco
- Interior/Exterior
- · Available in 5-gallon pails
- MPI #42 approval; Meets strict performance and aesthetic requirements
- VOC compliant in all regulated areas (<100 g/L)



Scan to view the Technical Data Sheet



#### PERMA-CRETE® 100% ACRYLIC TEXTURE COATING - MEDIUM 4-60

#### -00

- 100% acrylic texture coating
- Medium texture
- For use on horizontal and vertical, abovegrade, pre-cast and tilt-up masonry substrates
- · Minimizes surface imperfections
- · Provides a decorative appearance
- Ideal for use on brick, concrete, concrete block (CMU), masonry, metal, plaster, plywood, stone and stucco
- · Interior/Exterior
- · Available in 5-gallon pails
- MPI #42 approval; Meets strict performance and aesthetic requirements
- VOC compliant in all regulated areas (<100 g/L)

WARNING: Cancer - www.P65Warnings.ca.gov.



### PERMA-CRETE® 100% ACRYLIC TEXTURE COATING -LIGHTWEIGHT MEDIUM

#### 4-65

- · 100% acrylic texture coating
- Medium texture Vermiculite
- For use on horizontal and vertical, above-grade, pre-cast and tilt-up masonry substrates
- Minimizes surface imperfections
- · Provides a decorative appearance
- Ideal for use on brick, concrete, concrete block (CMU), masonry, metal, plaster, plywood, stone and stucco
- Interior/Exterior
- $\cdot$  Available in 5-gallon pails
- · VOC compliant in all regulated areas (<100 g/L)



#### PERMA-CRETE® 100% ACRYLIC TEXTURE COATING - COARSE 4-70

- · 100% acrylic texture coating
- · Coarse texture
- For use on horizontal and vertical, above-grade, pre-cast and tilt-up masonry substrates
- Minimizes surface imperfections
- · Provides a decorative appearance
- Ideal for use on brick, concrete, concrete block (CMU), masonry, metal, plaster, plywood, stone and stucco
- Interior/Exterior
- $\cdot$  Available in 5-gallon pails
- · VOC compliant in all regulated areas (<100 g/L)

## **VERTICAL ABOVE-GRADE TOPCOATS**

4-22XI, 4-26XI, 4-40XI, 4-422, 4-426, 4-440

PERMA-CRETE® high-performance, vertical above-grade topcoats can provide quality, protection and beauty on a range of masonry projects. These coatings protect your masonry job against severe sun, wind-driven rain, heat, humidity, dirt, salt, and efflorescence, thereby extending the repaint cycle.



### **PERMA-CRETE® HIGH BUILD** 100% ACRYLIC FLAT TOPCOAT

#### 4-22XI, 4-26XI, 4-40XI

- · A high build acrylic topcoat
- · For use on vertical, above-grade surfaces
- Apply to fresh concrete with a surface pH of 7 to 13; minimizes salt deposits
- Resists wind-driven rain with two coats @ 5 mils each
- Ideal for use on brick, concrete, concrete block (CMU), stucco and tilt-up
- Interior/Exterior
- · Available in 1- and 5-gallon pails
- VOC compliant in all regulated areas (<100 g/L)



## **PERMA-CRETE® HIGH BUILD** 100% ACRYLIC SATIN TOPCOAT

#### 4-422, 4-426, 4-440

- · A high build acrylic topcoat
- · For use on vertical, above-grade surfaces
- Apply to fresh concrete with a surface pH of 7 to 13; minimizes salt deposits
- Resists wind-driven rain with two coats @ 5 mils each
- Ideal for use on brick, concrete, concrete block (CMU), stucco and tilt-up
- Interior/Exterior
- · Available in 5-gallon pails
- VOC compliant in all regulated areas (<100 g/L)



Scan to view the Technical Data Sheet





Concrete stain can transform a drab driveway, patio or sidewalk with a great new look while protecting the surface from the elements.



## PERMA-CRETE<sup>®</sup> COLOR SEAL<sup>™</sup> WB INT/EXT ACRYLIC CONCRETE STAIN

#### 4-4210XI, 4-4220XI, 4-4240XI

- · Film forming, tintable, waterborne, acrylic concrete stain
- · Water and chemical resistant
- $\cdot$  Minimizes stains and discoloration
- · For use on above-grade, vertical and horizontal surfaces
- Ideal for use on masonry, concrete, brick, stone, stucco, mortar, non-glazed ceramic tile
- Interior/Exterior
- · Available in 1- and 5-gallon pails
- $\cdot$  Available in three bases
- · VOC compliant in all regulated areas (<100 g/L)



## **WATER REPELLENT** 4-6100

Provide maximum protection against the costly damaging affects of water, mildew, dirt and chemicals with PERMA-CRETE® AQUA-PEL<sup>™</sup> Clear Water Repellent. *Aqua-Pel* sealer is a concentrated water repellent designed for dilution with fresh water at the job site. *Aqua-Pel* sealer's ability to repel water helps extend the substrate life and reduces maintenance costs of the substrate. This penetrating sealer is easily applied to new or existing, vertical and horizontal, interior and exterior, concrete and masonry surfaces.



## PERMA-CRETE® AQUA-PEL™ CLEAR WATER REPELLENT

#### 4-6100

- · Clear, penetrating, non-film forming sealer
- · Water repellent
- For use on above-grade, vertical and horizontal surfaces
- Ideal for use on architectural concrete, concrete block, splitface block, pavers, stucco, porous and dense brick, clay tile, exposed aggregate concrete, sandstone and slate
- MPI #34 approval; Meets strict performance and aesthetic requirements
- Interior/Exterior
- · Available as a concentrate in 1-gallon (128 fl. oz.) bottle



# **PERMA-CRETE FEATURES & BENEFITS & CROSSOVER GUIDE**

Range Efflorescence-Resistan Interior / Exterior Use Temp -ow Temp Capability Ceiling\* / Vertical / Horizontal Use Application Temp F (air, surface, paint) Coverage (ft²/gal) / Restores Alkali-Resistant Water Repellent **Optimum Paint** Product Code VOC (g/L) Tintable Texture Binds / Chalky Sheen Color PATCHING COMPOUND PERMA-CRETE® PITT-FLEX® Elastomeric Patching 68°F@ 4-1000 I/F V/H Off-White 72 50-90°F 50°F Х Х No Flat Textured Varies Compound Knife Grade - Textured 50% RH PERMA-CRETE® PITT-FLEX® Elastomeric Patching 68°F@ 4-1001 I/E V/H Off-White Smooth No Flat 72 Varies 50-90°F 50°F Х Х Compound Knife Grade - Smooth 50% RH PERMA-CRETE® PITT-FLEX® Elastomeric Patching 68°F@ 4-1002 50-90°F 50°F I/F V/H Off-White 72 Smooth No Flat Varies Х Х Compound Brush Grade - Smooth 50% RH PERMA-CRETE® PITT-FLEX® Elastomeric Patching 68°F@ 50°F 4-1003 I/E V/H Off-White 72 50-90°F No Flat Varies Х Х Textured Compound Brush Grade - Textured 50% RH PRIMERS **Concrete and Stucco Primer** 4-503 Е C/V White 250-400 50-100°F 50-90°F 50°F Х Smooth Yes Flat 0-5 (60°) 85 Х Int./Ext. Alkali Resistant Primer 4-603XI I/E C/V White Non-Flat >5 99 400-500 35-100°F 50-90°F 35°F Smooth Yes Х Х **BLOCK FILLER** LTC (Low Temp.) Concrete Block & Masonry Surfacer 4-100XI I/E C/V White Smooth No Flat 60 80-100 35-100°F 50-90°F 35°F х х PRIMERS/SEALERS Int./Ext. Acrylic Masonry Surface Sealer - Clear 4-808 I/E C/V Clear Smooth No Satin/Flat 228 200-400 35-100°F 50-85°F 35°F Х I/E Х Int./Ext. Acrylic Masonry Surface Sealer - Pigmented 4-809 C/V Pigmented Smooth Yes Satin/Flat 231 200-400 35-100°F 50-85°F 35°F WATER REPELLENT Clear 329 as Х Aqua-Pel<sup>™</sup> Clear Water Repellent 4-6100 I/E C/V/H No N/A 40-175 50-100°F 50-90°F 50°F Smooth Concentrate applied **CLEAR TOPCOAT SEALER** Plex-Seal<sup>™</sup> WB Int./Ext. Clear Sealer 4-6200XI I/E C/V/H Clear Smooth No Satin 152 300-500 35-100°F 50-90°F 35°F Х Х ELASTOMERIC TOPCOAT 4-110XI PITT-FLEX® Elastomeric Coating - Smooth Ε C/V White Flat 1-7 (60°) 98 100-135 50-100°F 50-90°F 50°F Х Х Smooth Yes 4-140XI 100-135 Х PITT-FLEX® Elastomeric Coating - Smooth Ε C/V White Smooth Yes Flat 1-7 (60°) 98 50-100°F 50-90°F 50°F Х TEXTURED COATINGS 100% Acrylic Textured Coatings - Fine 4-50 I/E C/V White Fine Yes Flat 0-3 (85°) 57 125-135 50-100°F 50-90°F 50°F Х Х Medium -100% Acrylic Textured Coatings - Medium (Hard) Flat 0-3 (85°) 4-60 I/E C/V White Yes 56 125-135 50-100°F 50-90°F 50°F Х Х Hard Medium 100% Acrylic Textured Coatings - Medium (Soft) 4-65 I/F C/V White Flat 0-3 (85°) 58 125-135 50-100°F 50-90°F 50°F Yes Soft 100% Acrylic Textured Coatings - Coarse 4-70 I/F C/V White Flat 0-3 (85°) 56 125-135 50-100°F 50-90°F 50°F Х Coarse Yes Х **VERTICAL ABOVE-GRADE TOPCOATS** High Build 100% Acrylic Flat Topcoat 4-22XI I/E C/V White Smooth Yes Flat 0-3 (85°) 98 125-225 35-100°F 50-90°F 35°F Х Х C/V High Build 100% Acrylic Flat Topcoat 4-26XI I/E White Flat 0-3 (85°) 98 125-225 35-100°F Smooth Yes 50-90°F 35°F Х Х High Build 100% Acrylic Flat Topcoat 4-40XI I/E 125-225 35-100°F C/V White Smooth Yes Flat 0-3 (85°) 98 50-90°F 35°F Х Х High Build 100% Acrylic Satin Topcoat 4-422 I/E V/H <100 35-100°F White Yes Satin 125 to 225 65°F 35°F Х Smooth Х High Build 100% Acrylic Satin Topcoat 4-426 I/E V/H White Smooth Yes Satin <100 125 to 225 35-100°F 65°F 35°F Х Х High Build 100% Acrylic Satin Topcoat 4-440 I/E V/H White Smooth Yes Satin <100 125 to 225 35-100°F 65°F 35°F Х Х **CONCRETE STAIN** Color Seal™ WB Int./Ext. Acrylic Concrete Stain 4-4210XI I/E C/V/H White/Pastel Smooth Yes Satin 184 Up to 800 35-100°F 50-90°F 35°F Х Color Seal<sup>™</sup> WB Int./Ext. Acrylic Concrete Stain 4-4220XI I/E C/V/H 50-90°F 35°F Х Midtone Smooth Yes Satin 196 Up to 800 35-100°F

Color Seal™ WB Int./Ext. Acrvlic Concrete Stain

4-4240XI

I/E

C/V/H

Ultra Deep

Smooth

Satin

Yes

196

Up to 800

35-100°F

50-90°F

35°F

χ

FEATURES AND BENE

FITS							SUBSTRATE																					
Wind-Driven Rain-Resistant	Water Vapor Permeability (dry cup)	Flexibility	UV-Resistant	Elongation	Mildew-Resistant	Stain Blocking	Chemical-Resistant ***	Hot Tire-Resistant	Salt Spray	Accelerated Weathering	Dry Time (to recoat)	Self Priming	Lightweight	Adhesion	Brick	Concrete	Concrete / Cinder Block	Fiber Cement Siding	Masonry Surfaces	Stucco	Tilt-Up	Exposed Aggregate	Split Face Block	Non-Glazed Clay /	Slate, Sandstone	Wood	Plaster	Wallboard
		Х			Х						24 hours			Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	х
		Х			х						24 hours			х	Х	х	х	х	х	х	х	х	х	х	х	х	х	х
		х			Х						24 hours			х	х	х	Х	х	Х	х	х	Х	х	Х	х	х	х	х
		х			х						24 hours			Х	х	Х	х	Х	Х	Х	Х	х	Х	Х	Х	Х	Х	x
					Х						1-2 hours			Х	Х	Х	Х	Х	Х	Х	Х							
		Х	Х		Х	Х					1-24 hours (24 for max. stain resist.)			х	Х	Х	Х	Х	Х	Х	Х					Х	Х	х
Х											24 hours		Х	Х	Х	Х	Х	Х	Х	Х	Х							
											1-3 hours				Х	Х	Х	Х	Х	Х								
											1-3 hours				Х	х	х	Х	х	Х								
							Х	Х			2 coats wet-on-wet				Х	Х	Х		Х	Х	Х	Х	Х	Х	Х			
					Х		Х	Х		Х	2 hours			Х	Х	Х	Х		Х	Х	Х	Х		Х				
х	13	Х	Х	429% 2 coats	Х						4 hours min.				Х	Х	Х	Х	Х	Х	Х							
Х	13	Х	Х	429% 2 coats	Х						4 hours min.				Х	Х	Х	Х	Х	Х	Х							
X**	>15				Х						12-16 hours				Х	Х	Х	Х	Х	Х	Х							
X**					Х						12-16 hours				Х	Х	Х	Х	Х	Х	Х							
					Х						12-16 hours				Х	Х	Х	Х	Х	Х	Х							
					Х						12-16 hours				Х	Х	Х	Х	Х	Х	Х							
х	>15	Х	Х	240% 2 coats	Х						24 hours				х	Х	х	х	Х	х	Х							
х	>15	Х	Х	240% 2 coats	Х						24 hours				Х	х	х	Х	х	Х	х							
х	>15	Х	Х	240% 2 coats	Х						24 hours																	
Х	Х	Х	Х	200%	Х						4 hours	Х		Х														
X	X	X	X	200%	X						4 hours	X		X														
Х	Х	Х	Х	200%	Х						4 hours	Х		Х														
			X X		X X		X X	X X			6 hours 7 hours	X X		X X	X X	X	X		X X	X X	X X	X X		X X				
			X		X		X	X			8 hours	X		x	x	X	X		X	X	X	X		X				
			Λ		Λ		Λ	Λ			Onours	Λ		X	Λ	^	~		Λ	Λ	Λ	^		Λ				

#### **CROSSOVER GUIDE**

	Chossoven								
	SHERWIN WILLIAMS	BENJAMIN MOORE							
PATCHING COMPOUND									
PERMA-CRETE® PITT-FLEX® Elastomeric Patching Compound (4-1000)	SW Concrete & Masonry Smooth And Textured Elastomeric Patches	Moorlastic Elastomeric Patching Compound, 051-054							
PERMA-CRETE® PITT-FLEX® Elastomeric Patching Compound (4-1001)	SW Concrete & Masonry Smooth And Textured Elastomeric Patches	Moorlastic Elastomeric Patching Compound, 051-054							
PERMA-CRETE® PITT-FLEX® Elastomeric Patching Compound (4-1002)	SW Concrete & Masonry Smooth And Textured Elastomeric Patches	Moorlastic Elastomeric Patching Compound, 051-054							
PERMA-CRETE® PITT-FLEX® Elastomeric Patching Compound (4-1003) PRIMERS	SW Concrete & Masonry Smooth And Textured Elastomeric Patches	Moorlastic Elastomeric Patching Compound, 051-054							
Concrete and Stucco Primer (4-503)	LOXON® Concrete & Masonry Primer-Sealer, Lx02w0050	ULTRA SPEC <sup>®</sup> Interior/Exterior 100% Acrylic High Build Masonry Primer (N609)							
Int./Ext. Alkali Resistant Primer (4-603XI)	LOXON® Concrete & Masonry Primer-Sealer, Lx02w0050	ULTRA SPEC <sup>®</sup> Interior/Exterior 100% Acrylic High Build Masonry Primer (N609)							
BLOCK FILLER									
LTC (Low Temp.) Concrete Block & Masonry Surfacer (4-100XI)	LOXON® Acrylic Block Surfacer, Lx01	ULTRA SPEC® Hi-Build Masonry Block Filler 571							
PRIMERS/SEALERS									
Int./Ext. Acrylic Masonry Surface Sealer - Clear (4-808)	LOXON® Acrylic Conditioner, Lx03v0100 Clear	ULTRA SPEC® Masonry Interior/Exterior 100% Acrylic Sealer, 608							
Int./Ext. Acrylic Masonry Surface Sealer - Pigmented (4-809) WATER REPELLENT	LOXON® Acrylic Conditioner, Lx03w0100 Guide Coat White	ULTRA SPEC® Masonry Interior/Exterior 100% Acrylic Sealer, 608							
	Conflex 7% Siloxane Water Repellent, Cf31; H&C Hydro Defend Sx-7 Water Repellent;	Insl-X Multi-Surface Waterproofer Wps-1000; Coronado TEXCRETE®							
Aqua-Pel <sup>™</sup> Clear Water Repellent (4-6100)	H&C Hydro-Defend Water-Based Clear Concrete Waterproofer, 50.154	Silicone Water Repellent 194 Line							
CLEAR TOPCOAT SEALER									
Plex-Seal™ WB Int./Ext. Clear Sealer (4-6200XI)	Hydro-Defend Water-Based Concrete & Masonry Waterproofing Sealer, 50.14; H&C Clarishield Water-Based Natural Look Clear Concrete Sealer, 50.10	Corotech Clear Acrylic Sealer, V027							
ELASTOMERIC TOPCOAT									
PITT-FLEX® Elastomeric Coating - Smooth (4-110XI)	Conflex XI High Build Acrylic Coating, Cf11 Series; Conflex Sherlastic Elastomeric Masonry Coating, Cf16 Series; Conflex Flexible Concrete Waterproofer Smooth, Cf14 Series	ULTRA SPEC® Masonry Elastomeric Waterproofing Coating Flat 0359; Coronado TEXCRETE® Wb Texture Waterproofer Smooth Texture 3194 Line							
PITT-FLEX® Elastomeric Coating - Smooth (4-140XI)	Conflex XI High Build Acrylic Coating, Cf11 Series; Conflex Sherlastic Elastomeric Masonry Coating, Cf16 Series; Conflex Flexible Concrete Waterproofer Smooth, Cf14 Series	ULTRA SPEC® Masonry Elastomeric Waterproofing Coating Flat 0359; Coronado TEXCRETE® Wb Texture Waterproofer Smooth Texture 3194 Line							
TEXTURED COATINGS									
100% Acrylic Textured Coatings - Fine (4-50) 100% Acrylic Textured Coatings - Medium (Hard) (4-60)	Conflex Ultracrete Acrylic Textured Coating, Cf17w0801 Fine Extra White Conflex Ultracrete Acrylic Textured Coating, Cf17w0811 Medium Extra White	High-Build Exterior Texture Flat Fine 436 High-Build Exterior Texture Flat Medium 437							
100% Acrylic Textured Coatings - Medium (Soft) (4-65)	Conflex Ultracrete Acrylic Textured Coating, Cf17w0811 Medium Extra White	No Offset							
100% Acrylic Textured Coatings - Coarse (4-70)	Conflex Ultracrete Acrylic Textured Coating, Cf17w0821 Extra Coarse Extra White	No Offset							
VERTICAL ABOVE-GRADE TOPCOATS									
	LOVON® VD L v11 50 Sorias Elet: Lovon Solf Cleaning Actuals Conting Lut2 50 Series								
High Build 100% Acrylic Flat Topcoat (4-22XI)	LOXON® XP, Lx11-50 Series Flat; Loxon Self-Cleaning Acrylic Coating Lx13-50 Series, Flat; Conflex Acrylic Coating, Cf13-50 Series; Loxon Acrylic Coating, A24w300	REGAL® Select Exterior Paint - High Build Flat Finish N400							
High Build 100% Acrylic Flat Topcoat (4-26XI)	LOXON® XP, Lx11-50 Series Flat; Loxon Self-Cleaning Acrylic Coating Lx13-50 Series, Flat; Conflex Acrylic Coating, Cf13-50 Series; Loxon Acrylic Coating, A24w300	$REGAL^{\circledast}$ Select Exterior Paint - High Build Flat Finish N400							
High Build 100% Acrylic Flat Topcoat (4-40XI)	LOXON® XP, Lx11-50 Series Flat; Loxon Self-Cleaning Acrylic Coating Lx13-50 Series, Flat; Conflex Acrylic Coating, Cf13-50 Series; Loxon Acrylic Coating, A24w300	REGAL® Select Exterior Paint - High Build Flat Finish N400							
High Build 100% Acrylic Satin Topcoat (4-422)	LOXON® XP: has both Flat LX-11 Series and Satin, LX-21 Series LOXON® Self-Cleaning Acrylic: has both Flat LX-13 Series and Satin, LX-14 Series	REGAL® Select High Build Low Lustre, N401 and REGAL® Select High Build Soft Gloss, N403							
High Build 100% Acrylic Satin Topcoat (4-426)	LOXON® XP: has both Flat LX-11 Series and Satin, LX-21 Series LOXON® Self-Cleaning Acrylic: has both Flat LX-13 Series and Satin, LX-14 Series	REGAL® Select High Build Low Lustre, N401 and REGAL® Select High Build Soft Gloss, N403							
High Build 100% Acrylic Satin Topcoat (4-440)	LOXON® XP: has both Flat LX-11 Series and Satin, LX-21 Series LOXON® Self-Cleaning Acrylic: has both Flat LX-13 Series and Satin, LX-14 Series	REGAL® Select High Build Low Lustre, N401 and REGAL® Select High Build Soft Gloss, N403							
CONCRETE STAIN									
Color Seal™ WB Int./Ext. Acrylic Concrete Stain (4-4210XI)	H&C Colortop Water-Based Solid Color Concrete Stain, 20.10; H&C Colortop Water-Based Solid Color Concrete Stain 50, 20.10; H&C Heavy Shield Water-Based Solid Color Concrete & Driveway Enamel / Stain, 35.10	INSL-X TUFFCRETE® Wb Acrylic Waterproofing Concrete Stain Ccst-2xxx							
Color Seal™ WB Int./Ext. Acrylic Concrete Stain (4-4220XI)	H&C Colortop Water-Based Solid Color Concrete Stain, 20.10; H&C Colortop Water-Based Solid Color Concrete Stain 50, 20.10; H&C Heavy Shield Water-Based Solid Color Concrete & Driveway Enamel / Stain, 35.10	INSL-X TUFFCRETE® Wb Acrylic Waterproofing Concrete Stain Ccst-2xxx							
Color Seal™ WB Int./Ext. Acrylic Concrete Stain (4-4240XI)	H&C Colortop Water-Based Solid Color Concrete Stain, 20.10; H&C Colortop Water-Based Solid Color Concrete Stain 50, 20.10; H&C Heavy Shield Water-Based Solid Color Concrete & Driveway Enamel / Stain, 35.10	INSL-X TUFFCRETE® Wb Acrylic Waterproofing Concrete Stain Ccst-2xxx							

## **NOTES**



## TO LEARN MORE ABOUT PPG OR TO FIND A LOCATION NEAR YOU, PLEASE VISIT <u>PPGPAINTS.COM</u>.



PPG Architectural Finishes, Inc. • PPG • 400 Bertha Lamme Dr. • Cranberry Township, PA 16066 Technical Service: 1-800-441-9695 • Architect/Specifier: 1-888-PPG-IDEA • ppgpaints.com

© 2023 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Perma-Crete and Pitt-Flex are registered trademarks and Color Seal, Aqua-Pel and Plex Seal are trademarks of PPG Architectural Finishes, Inc. PG\_1009399 6/23