

## PPG Paint & Colorant Solidifier

Provides an environmentally acceptable way to dispose of unwanted water-based paint and colorants by quickly turning them into a solid for legal disposal. Provides a dramatic cost savings compared with the disposal of liquid paint

### Features and Benefits

- Easy-to-use and works in minutes
- Non-toxic (suitable for curbside disposal)
- Environmentally sound
- One bag will harden up to 2/3 of a gallon of left over paint and one 30lb pail will harden approximately 107 gallons
- No DOT shipping regulations

### Product Data

- Appearance: White granular
- Density: 25-31lbs / cubic foot
- 3.5 oz bag: solidifies up to 2/3 of a gallon (2.5L) of water-based paint
- 5 gallon: solidifies approximately 107 gallons of water-based paint.

### Packaging

3.5oz (99g) x 12 bags/ case  
30 lb (5 USGal18.9L) pail

PPG believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.  
Surface Solutions  
One PPG Place  
Pittsburgh, PA 15272  
[www.ppg.com/surfaceprep](http://www.ppg.com/surfaceprep)

### Recommended Use

- Disposal of any water-based product that otherwise is safe for disposal in a landfill when not in liquid form
- Disposal of latex paint
- Spills of the above materials

### Safety Precautions

Proper safety procedures should be followed at all times while handling this product. Refer to the Material Safety Data Sheet for important health/safety information before use.

MSDS are available through the DuraPrep® website, [www.ppg.com/surfaceprep](http://www.ppg.com/surfaceprep) or by calling 412-434-4515.

### Instructions

Gallon can: Stir or drill mix powder into the paint and mix thoroughly until the paint begins to stiffen.

Pail or drum: Harden in 4-8 inch lifts by adding the paint, drill mixing the powder in, allowing the paint to begin to harden for 10-15 minutes and repeating the process with another 4-8 inches of paint. Do not leave drill in pail/drum.

Dispose of hardened paint in accordance with local regulations.