



Prep™ 120 Concentrated Multi-Purpose Cleaner

A highly concentrated, economical cleaner capable of handling many types of cleaning applications in industrial, commercial, automotive and marine applications.

Features and Benefits

- Safe on most painted surfaces, metals, plastics, rubber, vinyl, glass, and more
- Can be sprayed, brushed, mopped, or dipped
- Water-based, non-flammable, biodegradable
- Contains No TAP's or HAP's (Toxic/Hazardous Air Pollutants)
- No DOT shipping restrictions

Recommended Use

- Paint preparation on structures
- Removing dirt, soot, road grime, scuffs, tire marks, and other common contaminants
- Ideal for injection through a pressure washer
- Transportation vehicles
- Office equipment
- General cleaning applications
- Clean-up after DuraPrep® coating removal

Product Data

Appearance:	Clear liquid
Specific Gravity:	1.0
Boiling Point:	215°F (102°C)
Freezing Point:	25°F (-4°C)
pH:	11
Flash Point:	221°F (105°C)
Coverage:	50 to 500 sq. ft/gal (Theoretical)
VOC (Concentrate):	None
Shelf Life:	24 months

Safety Precautions

Proper safety procedures should be followed at all times while handling this product. Refer to the Material Safety Data Sheet for important health/safety information before use. **For Professional Use Only; Not Intended for Household Use.**

MSDS are available through the DuraPrep® website, www.ppg.com/surfaceprep or by calling 412-434-4515.

Packaging

1 gal (3.8 L)	
5 gal (19.0L)	
55 gal (210 L)	Special Order
330 gal (1254 L)	Special Order

Limitations of Use

Surface temperatures should be between 32°F to 120°F (0°C and 49°C).



Directions for Use:

Typical Dilution Ratios:

- General Purpose Cleaning:
2-4 oz. **Prep™120**: 1-gal water
- Light Duty Cleaning (General Pressure Washing):
8-12oz. **Prep™120**: 1-gal water
- Medium Duty Cleaning: (Transportation Vehicles, Fireplace soot)
20-30oz. **Prep™120**: 1-gal water
- Heavy Duty Cleaning
1/2 gal. **Prep™120**: 1-gal water

Test Area: Always prepare a test area to determine product performance, coverage and applicable dilution ratios, as well as the suitability of product for the paint and the substrate.

Mixing: After appropriate dilution is determined by test patch, add the proper amount of **Prep™120** to water and agitate.

Application & Removal: Apply properly diluted **Prep™120** with mop, brush, or spray. Allow to remain on surface for ½ - 5 minutes, agitate the surface with a brush, and rinse with water. For best results, use a pressure washer.

Prep™120 is designed to create a very strong cleaning solution when added through a standard 10:1 injection port on a pressure washer.

Re-Coating: After sufficient drying time, ensure the surface is dry and dust-free prior to recoating in accordance with good painting practice and the coating manufacturer's instructions.

PPG believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Surface Solutions
One PPG Place
Pittsburgh, PA 15272
www.ppg.com/surfaceprep